

# DSM-506 DIGITAL SURVEY METER/Internal Detector

The DSM-506 boasts an oversized digital display. It has a unique counts to dose capability allowing the user to quickly change from count rate to dose rate and back by the flip of a toggle switch. Other features include a scaler for counts per unit of time, display error indications and audible/visual ALARMS. It has an external probe connector and internal Energy Compensated GM Tube that has a dose rate range of 50  $\mu$ R/hr-2000 mR/hr.

## FEATURES:

- ◆ **LARGE DIGITAL DISPLAY**
- ◆ **AUTO RANGING UNITS**
- ◆ **DUAL MODE CAPACITY FOR DOSE RATE & COUNT RATE**
- ◆ **AUDIBLE/VISUAL ALARMS**



## **DSM-506 SPECIFICATIONS:**

Dose/Counts Switch	Change Dose Rate to Count Rate by Toggling an External Switch
Display	LCD 4-Digit x .75" LCD w/LED Backlight
Internal Detector	Energy Compensated GM Tube
Energy Range	60 keV – 3 MeV
Internal Detector Dose Range	50 $\mu$ R/hr - 2000 mR/hr or equivalent Sv/hr
External Probe Connector	All Johnson Probes
CPM Range	0-999.9 Kcpm or Kcps
Probe Linearization	Internal adjust for calibration constant and dead time
Scaler Ranges	0-999.9 Kcounts
Scaler Count Time Ranges	10-2550 Seconds (10 second increments)
Alarms	5-95% of Range
Diagnostics	Low Battery, Over-range - Audible & Visual Alarms
Range Adjustment	Auto-Ranging All Scales
Electrical Non-Linearity	< 5% Full Scale
Response Time	Fast - 10-2550 Seconds (adjustable) / Slow 10-250 seconds (adjustable)
Drift	< 5%
Environmental	-20°F[-28°C] to 140°F[60°C]   5-95% RH IPX4 Housing
High Voltage Adjustable	400-1250 VDC   Regulation +-1%
Battery	6 - "AA" Alkaline (nominal 200hrs Operation)
Dimensions	5.25"(14cm) H X 4" (10cm) W x 7"(18cm) L
Weight	2.5 lbs. (1.2 Kilos)



**PACIFIC-TEC SCIENTIFIC PTE LTD**

33 Ubi Avenue 3, #06-48 Vertex Tower A, Singapore 408868

Tel: +65 6342 1530 Fax: +65 6342 1531 WhatsApp: +65 8874 6269

Email: sales@pacific-tec.sg

Website: www.pacific-tec.sg